

AQUA FLO[®]

PLATINUM

P-SW SERIES

String Wound Filter Cartridges

The Aqua Flo P-SW cartridge filters are manufactured from polypropylene cord which is wound around the polypropylene core.

These cartridge filters are an economical solution for reduction of sediment, sand, rust and scale particles from the drinking water.

FEATURES / BENEFITS:

- ◆ String wound filters reduces sediment from a variety of liquids
- ◆ Low pressure drop
- ◆ Withstands high temperatures
- ◆ Wide chemical compatibility
- ◆ Available in four sizes: 2.5x10"; 2.5x20"; 4.5x10"; 4.5x20"
- ◆ Universal fit – Fits most standard water filter housings
- ◆ Available in four micron ratings: 1; 5; 20; 50

SPECIFICATIONS:

- ◆ Filter Media – Polypropylene
- ◆ Core – Polypropylene
- ◆ Temperature Rating – 40 - 140°F (4 -60°C)

APPLICATIONS (For water filtration only):

- ◆ Commercial/Residential Drinking Water Filtration
- ◆ RO Pre-filtration
- ◆ Cooling Tower Filtration
- ◆ Chill Water Loop Filtration
- ◆ Food & Beverage Filtration
- ◆ Industrial Water Filtration



This String Wound Filter is Tested and Certified by NSF International against NSF/ANSI Standard 42 for material and structural integrity requirements.

COMPONENT



“An economical solution for reduction of sediment, sand, rust and scale particles from the drinking water.”

P-SW SERIES

String Wound Filter Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM #	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
36159	P-SW-1-10	2.5" x 10" (63.5 x 254 mm)	50	0.4	1	5 US GPM (19 LPM)
36109	P-SW-5-10	2.5" x 10" (63.5 x 254 mm)	50	0.4	5	8 US GPM (30.3 Lpm)
36160	P-SW-20-10	2.5" x 10" (63.5 x 254 mm)	50	0.4	20	16 US GPM (60.6 LPM)
36102	P-SW-50-10	2.5" x 10" (63.5 x 254 mm)	50	0.8	50	20 US GPM (75.7 LPM)
36169	P-SW-1-20	2.5" x 20" (63.5 x 508 mm)	25	0.6	1	10 US GPM (38 LPM)
36161	P-SW-5-20	2.5" x 20" (63.5 x 508 mm)	25	0.8	5	16 US GPM (60.6 LPM)
36162	P-SW-20-20	2.5" x 20" (63.5 x 508 mm)	25	0.8	20	30 US GPM (113.4 LPM)
36163	P-SW-50-20	2.5" x 20" (63.5 x 508 mm)	25	0.8	50	30 US GPM (113.4 LPM)
36164	P-SW-1-10BV	4.5" x 10" (114.3 x 254 mm)	20	1.4	1	10 US GPM (38 LPM)
36138	P-SW-5-10BV	4.5" x 10" (114.3 x 254 mm)	20	1.4	5	20 US GPM (75.7 LPM)
36165	P-SW-20-10BV	4.5" x 10" (114.3 x 254 mm)	20	1.4	20	20 US GPM (75.7 LPM)
36166	P-SW-50-10BV	4.5" x 10" (114.3 x 254 mm)	20	1.4	50	20 US GPM (75.7 LPM)
36141	P-SW-1-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.8	1	30 US GPM (113.4 LPM)
36142	P-SW-5-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.8	5	30 US GPM (113.4 LPM)
36167	P-SW-20-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.8	20	30 US GPM (113.4 LPM)
36168	P-SW-50-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.8	50	30 US GPM (113.4 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.

AQUA FLO®

A Division of



Your Local Water Specialist