

The Best Performing Pressure Tank in the Industry!



The World's First & Only 100% Robotic Tank Manufacturing Line

With over 1,000,000 tanks without a failure we know that our tanks perform in the field! Imagine never having to deal with another leaky tank! Tank liners are blow-molded from high quality, high strength engineering materials.

Each tank is wrapped with miles of continuous high strength glass rovings with the most advanced computer aided winding equipment in the world! The Petwa NSF Certified fiberglass reinforced pressure tank is designed to eliminate any potential leaks since there are no welds, joints, or seams in the tank liner.

Petwa tanks offer unmatched strength, finish durability and resistance to temperature and corrosion.



Fiberglass Tanks Specifications:

Standard Pressure Tank Models											
Tank Size (in)	Volume			Weight (lbs)	Opening		Base	Dimensions(in)			
	Liters	Cu.ft.	Gallons		Top	Bottom		La	Lb	Da	Db
	05x17*	3.8	0.13		1.0	2.7		2.5"-8-NPSM	N/A	std.	16.7
05x20*	4.5	0.18	1.2	2.9	2.5"-8-NPSM	N/A	std.	20.3	20.3	4.8	5.1
06x18*	6.65	0.23	1.8	3.8	2.5"-8-NPSM	N/A	std.	18.2	18.0	6.1	6.5
07x13*	6.3	0.22	1.7	3.4	2.5"-8-NPSM	N/A	std.	13.2	13.0	7.2	7.5
07x17*	8.5	0.3	2.2	4.1	2.5"-8-NPSM	N/A	std.	17.2	17.0	7.2	7.5
07x30*	15.8	0.56	4.2	6.2	2.5"-8-NPSM	N/A	std.	30.2	30.0	7.2	7.5
07x35*	19.1	0.67	5.0	6.8	2.5"-8-NPSM	N/A	std.	35.4	35.1	7.2	7.5
08x15*	9.3	0.33	2.5	4.1	2.5"-8-NPSM	N/A	std.	15.2	15.0	8.1	8.5
08x17*	10.5	0.37	2.8	4.5	2.5"-8-NPSM	N/A	std.	17.2	17.0	8.1	8.5
08x18*	11.5	0.41	3.0	5.3	2.5"-8-NPSM	N/A	std.	18.2	18.0	8.1	8.5
08x24*	16.6	0.59	4.4	5.9	2.5"-8-NPSM	N/A	std.	24.2	24.0	8.1	8.5
08x30	21	0.74	5.5	7.1	2.5"-8-NPSM	N/A	std.	30.3	30.1	8.1	8.5
08x35	23.6	0.83	6.2	7.8	2.5"-8-NPSM	N/A	std.	35.3	35.1	8.1	8.5
08x44	31.3	1.11	8.3	10.3	2.5"-8-NPSM	N/A	std.	44.2	44.0	8.1	8.5
09x35	II 31.6	1.12	8.3	10.1	2.5"-8-NPSM	N/A	std.	35.4	35.1	9.2	9.5
09x42*	II 38.5	1.36	10.2	11.8	2.5"-8-NPSM	N/A	std.	42.3	42.0	9.2	9.5
09x48	II 44.6	1.58	11.8	13.4	2.5"-8-NPSM	N/A	std.	48.3	48.1	9.2	9.5
10x15*	14	0.49	3.7	5.9	2.5"-8-NPSM	N/A	std.	15.1	15.0	10.2	10.6
10x24*	24.8	0.88	6.6	8.7	2.5"-8-NPSM	N/A	std.	24.0	23.9	10.2	10.6
10x26*	27.3	0.96	7.2	10.0	2.5"-8-NPSM	N/A	std.	26.1	26.0	10.2	10.6
10x30*	32.30	1.14	8.5	10.8	2.5"-8-NPSM	N/A	std.	30.9	30.0	10.2	10.6
10x35	II 38.3	1.35	10.1	10.8	2.5"-8-NPSM	N/A	std.	35.2	35.1	10.2	10.6
10x44	II 48.8	1.72	12.9	13.5	2.5"-8-NPSM	N/A	std.	44.1	44.0	10.2	10.6
10x47	53.2	1.88	14.1	13.8	2.5"-8-NPSM	N/A	std.	47.2	47.0	10.2	10.6
10x54	II 61	2.16	16.1	15.2	2.5"-8-NPSM	N/A	std.	54.4	54.3	10.2	10.6
11x35*	46.7	1.65	12.3	12.5	2.5"-8-NPSM	N/A	std.	35.6	35.1	11.2	11.6
11x44*	59.8	2.11	15.8	15.8	2.5"-8-NPSM	N/A	std.	44.5	44.0	11.2	11.6
12x48*	78.54	2.78	20.8	17.8	2.5"-8-NPSM	N/A	std.	48.5	48.0	12.1	12.4
12x52	84.7	2.99	22.4	19.6	2.5"-8-NPSM	N/A	std.	52.7	52.1	12.1	12.4
13x54	105.7	3.73	27.9	22.6	2.5"-8-NPSM	N/A	std.	55.0	54.5	13.2	13.7
14x52	115	4.06	30.4	28.2	2.5"-8-NPSM	N/A	std.	52.9	50.9	14.5	N/A
14x52	115	4.06	30.4	28.2	4"-8-UN	N/A	std.	52.9	50.9	14.5	N/A
14x65	148	5.23	39.1	33.6	2.5"-8-NPSM	N/A	std.	65.9	63.9	14.5	N/A
14x65	148	5.23	39.1	33.6	4"-8-UN	N/A	std.	65.9	63.9	14.5	N/A
16x24*	56.98	2.01	15.1	14.7	2.5"-8-NPSM	N/A	std.	24.6	22.5	16.3	N/A
16x24*	56.98	2.01	15.1	14.7	4"-8-UN	N/A	std.	24.6	22.6	16.3	N/A
16x36*	98.1	3.47	25.9	22.3	2.5"-8-NPSM	N/A	std.	38.1	36.1	16.3	N/A
16x36*	98.1	3.47	25.9	22.3	4"-8-UN	N/A	std.	38.2	36.2	16.3	N/A
16x44*	131.6	4.65	34.8	27.4	2.5"-8-NPSM	N/A	std.	48.8	46.9	16.3	N/A
16x44*	131.6	4.65	34.8	27.4	4"-8-UN	N/A	std.	48.8	46.9	16.3	N/A
16x52*	148.3	5.24	39.2	32.7	2.5"-8-NPSM	N/A	std.	54.2	52.2	16.3	N/A
16x52*	148.3	5.24	39.2	32.7	4"-8-UN	N/A	std.	54.1	52.2	16.3	N/A
16x65	188.6	6.66	49.8	40.6	4"-8-UN	N/A	std.	67.1	65.2	16.3	N/A
18x36*	138	4.88	36.5	42.8	4"-8-UN	N/A	FRP St	39.4	37.0	19.5	N/A
18x65	257	9.08	67.9	56.5	4"-8-UN	N/A	FRP St	67.8	65.4	19.5	N/A
18x53	211	7.46	55.7	43.9	4"-8-UN	N/A	FRP St	56.4	54.0	19.5	N/A
21x36*	164	5.8	43.3	41.5	4"-8-UN	N/A	FRP St	39.4	37.6	22.0	N/A
21x53*	253	8.94	66.8	57.0	4"-8-UN	N/A	FRP St	56.5	54.6	22.0	N/A
21x62	330	11.66	87.2	68.3	4"-8-UN	N/A	FRP St	67.8	65.9	22.0	N/A
24x72	494	17.46	130.5	94.4	4"-8-UN	N/A	FRP St	75.5	73.8	24.3	N/A
30x72	D 745	26.33	196.8	155.5	4"-8-UN	4"-8-UN	Tripod	84.3	71.3	30.7	N/A
30x72	D 734	25.94	193.9	185.2	6-Flange	6-Flange	Tripod	86.2	75.8	30.7	N/A
36x72	D 1008	35.62	266.3	211.7	4"-8-UN	4"-8-UN	Tripod	84.6	72.4	36.1	N/A
36x72	D 993	35.09	262.4	249.2	6-Flange	6-Flange	Tripod	89.0	76.4	36.1	N/A
42x72	D 1460	51.59	385.7	339.6	6-Flange	6-Flange	Tripod	94.9	81.9	46.1	N/A
48x72	D 1934	68.34	511.0	363.8	6-Flange	6-Flange	Tripod	94.5	81.9	48.4	N/A
63x86	D 3050	107.77	805.8	672.5	6-Flange	6-Flange	Tripod	94.5	81.9	63.4	N/A

* Non Stocked Items

Features:

- ➔ Fiberglass reinforced polyethylene tanks
- ➔ Blow-molded polyethylene liner wound with high performance fibreglass/epoxy
- ➔ Complete seamless molding technology
- ➔ Threaded inlet made from 30% glass filled PP for superior strength
- ➔ 1/3 the weight of steel tanks
- ➔ Attractive high-gloss finish
- 0 Corrosion resistant
- ➔ Strict dimension tolerances
- ➔ Tanks 5" to 24" are NSF/ANSI 44 Certified for Materials & Structural Integrity
- ➔ Tanks 24" to 63" (>83.5 Gal) are NSF/ANSI 61 Certified for Drinking Water System Components - Health Effects
- ➔ 10 Year Warranty Tanks up to 24"
- ➔ 5 Year Warranty Tanks 30" and larger
- ➔ Solvent free central tube with spun weld collector eliminates use of glue and solvents
- ➔ Available in Natural, Black and Blue

Your Local Water Treatment Professional



A Division of



TOLL-FREE: 1-877-288-9888
www.petwawater.com