

## PW765 Series Automatic Whole House Water Filter

Problem water is no problem with our full line of Petwa Water Automatic Filters. Eliminate iron, sediment, bad tastes, stains and odors, as well as, color caused by organics.

## **Types of Filters:**

Taste & Odor - Remove bad tastes and odors caused by chlorine & organics

**Multi Media -** Eliminate suspended sand and silt that makes water cloudy

**NexSand** - Remove suspended solids, Ferric Hydroxide (Red Water Iron) or Sediment from your well or water system down to 5 Microns. Nexsand has proven extremely effective and will provide double the service flow of Multi Media or Sand Filters.

**Neutralizing** - Raise the pH of acidic water to neutralize corrosiveness and protect fixtures, pipes and appliances

**Birm -** Remove soluble or precipitated iron without the use of expensive or messy chemicals

Manganese Greensand - Iron, manganese and sulfur are oxidized into solids and trapped in the filter bed where they get flushed to the drain

**Chloramines** - This two tank system uses special catalytically enhanced carbon and provides improved bed depth and contact time for more effective reduction of chloramines.

Clean, Clear and Odor Free





Model	Media Cu Ft	Flow Rate USGPM			pH Correction	Iron Removal	KMnO4 Regen	Micron	Mineral	Pipe Size	Ship Weight
		Service	Peak	Backwash	Dance	Capacity (ppm)	(oz)	Rating	Tank Size	Inches	(Lbs)
Iron Filters - Manganese Greensand Plus											
PW 765IF-75	0.75	3.0	4.0	3.5		4,500	2.0	-	8 x 44	3/4" - 1"	113
PW 765IF-100	1.0	3.0	5.0	4.0		6,000	4.0	-	9 x 48	3/4" - 1"	129
PW 765IF-150	1.5	4.0	8.0	5.0		9,000	6.0	-	10 x 54	3/4" - 1"	179
Maximum Removal Amounts: Combination of Iron x 1, Manganese x 2, H2S x 3 = 10 ppm; Hydrogen Sulphide = 3.0 ppm; Iron (Ferrous) = 7.0 ppm; Manganese = 5.0 ppm; Bacterial Iron = 0.0 ppm; Min pH = 7.0											
Iron Filters - Birm											
PW 765BM-75	0.75	3.0	4.0	3.5		-	-		8 x 44	3/4" - 1"	67
PW 765BM-100	1.0	3.0	5.0	4.0		-	-		9 x 48	3/4" - 1"	79
PW 765BM-150	1.5	4.0	8.0	5.0		-	-		10 x 54	3/4" - 1"	101
Taste & Odor Filters											
PW 765TO-75	0.75	4.0	5.0	3.5		-	-		8 x 44	3/4" - 1"	50
PW 765TO-100	1.0	4.0	6.0	4.0		-	-		9 x 48	3/4" - 1"	60
PW 765TO-150	1.5	5.0	7.0	5.0		-	-		10 x 54	3/4" - 1"	78
Neutralizing Filters	S								<u> </u>		
PW 765NU-75	0.75	2.0	4.0	4.0	6.0 - 6.9 TDS >200	-	-		8 x 44	3/4" - 1"	93
PW 765NU-100	1.0	3.0	6.0	5.0	6.0 - 6.9 TDS >200	-	-		9 x 48	3/4" - 1"	120
PW 765NU-150	1.5	4.0	10.0	7.0	6.0 - 6.9 TDS >200	-	-		10 x 54	3/4" - 1"	164
Sediment Turbidity Multi-Media Filters											
PW 765MM-75	0.75	4.0	5.0	3.5		-	-	15 -20 μ	8 x 44	3/4" - 1"	79
PW 765MM-100	1.0	5.0	7.0	4.0		-	-	15 -20 μ	9 x 48	3/4" - 1"	118
PW 765MM-150	1.5	7.0	10.0	7.0		-	-	15 -20 μ	10 x 54	3/4" - 1"	144
Nexsand Turbidity	Filters										
PW 765NEX-75	0.75	4.0	6.0	5.0		-	-	3 - 5 μ	8 x 44	3/4" - 1"	90
PW 765NEX-100	1.00	5.0	8.0	7.0		-	-	3 - 5 μ	9 x 48	3/4" - 1"	135
Chloramines Redu	ction Filt	ers (Cataly	tic Carbor	) Dual Tank	(						
PW 765CLA-75	0.75	4.0	6.0	3.5		-	-		8 x 44	3/4" - 1"	100
PW 765CLA-100	1.00	5.0	8.0	4.0		-	-		9 x 48	3/4" - 1"	120
PW 765CLA-150	1.50	8.0	10.0	5.0		-	-		10 x 54	3/4" - 1"	155



A Division of

Canature

WaterGroup

Your Local Water Treatment Professional

TOLL-FREE: 1-877-288-9888 www.petwawater.com