

BIF Series Chemical Free Iron Filter

Remove Stubborn Iron Without Chemicals

Incoming raw water passes through a compressed pocket of air contained in the first tank. The air precipitates the iron into solid form and is removed when it passes through the filters media bed contained in the second tank. The media acts as a catalyst in the reaction between iron and oxygen that also causes the iron to precipitate into a solid.

As more water passes through the unit the air becomes depleted and the media becomes overloaded with the iron. Periodic automatic regeneration replenishes the supply of air and cleans the media of filtered iron.



Clean, Clear
Iron-Free
Water



Features:

- ➔ Exclusive NSF Certified electronic control valve (systems available with Petwa PW89 Series control valve)
- ➔ Natural oxidation removes iron, sulfur and manganese without chemicals, air pumps or a venturi
- ➔ Low maintenance two tank system
- ➔ Regenerate less frequently than traditional iron filters using up to 50% less water than manganese greensand filters
- ➔ Lifetime Warranty on NSF Certified fibreglass tanks
- ➔ Seven Year Warranty on NSF Certified control valve
- ➔ Meter Immediate, Meter Delayed, Meter with Day Override, Vacation and Calendar Clock mode
- ➔ Adjustable cycle times
- ➔ Unique bypass with an integrated space saving turbine meter and sample port on the inlet. One-piece design avoids meter jamming
- ➔ Time saving quick connect fittings on bypass
- ➔ Quick connect drain line o-ring eliminates need for Teflon
- ➔ Power cord even has quick connect for easy valve spin on
- ➔ Hose clamp and 10' of drain tubing included



PW89 Series High Flow valve

- ➔ True 1" porting for high flow rates up to 18" systems. Ideal for larger homes.
- ➔ Large Backlit LCD display screen with 4 line / 80 character touch pad screen.
- ➔ Seven Year Warranty

Specifications	BIF-100	BIF-150	BIF-200	BIF-300	BIF-400	BIF-500
	BIFMN-100	BIFMN-150	BIFMN-200	BIFMN-300	BIFMN-400	BIFMN-500
Typical Service Flow Rate	3.0 gpm	4.0 gpm	5.0 gpm	6.0 gpm	7.0 gpm	9.0 gpm
Peak Flow Rate	6.0 gpm	10.0 gpm	12.0 gpm	14.0 gpm	16.0 gpm	18.0 gpm
Backwash Flow Rate	5.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm	14.0 gpm	21.0 gpm
Filter Media Volume (ft3)	1.0 ft	1.5 ft	2.0ft	3.0 ft	4.0 ft	5.0 ft
Filter Tank Size	10x44	10x54	12x52	14x65	16x65	18x65
Air Contact Tank Size	10x44	10x54	12x52	14x65	14x65	14x65
Shipping Weight	BIF: 170 lbs	BIF: 200 lbs	BIF: 381 lbs	BIF: 409 lbs	BIF: 522 lbs	BIF: 640 lbs
	BIFMN: 168 lbs	BIFMN: 197lbs	BIFMN: 357 lbs	BIFMN: 402 lbs	BIFMN: 518 lbs	BIFMN: 640 lbs
Media Loaded	Yes	Yes	No	No	No	No
Maximum Iron	30.0 ppm					
Hydrogen Sulfide	BIF Model 1.0 ppm / BIFMN 3.0 ppm					
Mangansese	BIF Model 0.0 ppm / BIFMN Models up to 1.0 ppm					
Iron Bacteria Removal	No					
pH	BIF Models pH 7.0 - 8.5 / BIFMN Models pH 6.5 -7.5					
Plumbing Connections	1" 90 Degree Elbow NPT Connectors					
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA					
Water Temperature	Min 39 - Max. 100° F					
Water Pressure	Min. 20 - Max. 125 psi					



A Division of



TOLL-FREE: 1-877-288-9888
www.petwawater.com

Your Local Water Treatment Professional